



XF1 INTEGRA 150 TRAIL

TECHNICAL SPECIFICATIONS

Motor	Brose Drive-S 36 Volt, Max power: 250 Watt, Torque: 90 Nm
Battery	Fantic Integra, Lithium Ion, 36 Volt, 630Wh
Display	Brose-Marquardt multifunctional display & push-assistance selection unit
Frame	Aluminium Enduro frame, CNC parts, Sizes: S - M - L
Fork	RockShox Recon RL 29" 150mm
Shock	RockShox Deluxe Select+ T205x57,5 Air
Groupset	SRAM SX e-click Eagle 12-speed
Crankset	Miranda Delta Isis 165mm
Cassette	Sram SX Eagle 12-speed 11-50
Chain	Sram SX Eagle 12-speed
Front brake	Sram Level, 2-piston, Hydraulic Disc Brake, CleanSweep 200mm disc
Rear brake	Sram Level, 2-piston, Hydraulic Disc Brake, CleanSweep 200mm disc
Tires	Schwalbe SMART-SAM, front 29" x 2.25 / Rear 27.5" x 2.6
Wheels	GMP by Fantic, T-ready
Front hub	Sram 716 RS, 110 mm, Boost, thru axle 15mm
Rear hub	Sram 716 RS, 148 mm, Boost; thru axle 12mm
Handlebar	FSA Logo Ø31.8 L.760mm Rise15
Stem	FSA Logo Ø31.8 L.60mm
Seatpost	Switch, height-adjustable dropper, S-M(100mm), L(125mm)
Saddle	SelleItalia X-Land Flow