



XF2 INTEGRA

TECHNICAL SPECIFICATIONS

Motor	Brose Drive-S 36 Volt, Max power: 250 Watt, Torque: 90 Nm
Battery	Fantic Integra, Lithium Ion, 36 Volt, 630Wh
Display	Brose-Marquardt multifunctional display & push-assistance selection unit
Frame	Aluminium frame, CNC parts, Sizes: S - M - L
Fork	RockShox Recon RL, 120mm
Groupset	SRAM SX e-click 12-speed
Crankset	MirandaDelta Isis 165mm Asym
Cassette	Sram SX Eagle 12-speed 11-50
Chain	Sram SX Eagle 12-speed
Front brake	Sram Level, 2-piston, Hydraulic Disc Brake, CleanSweep 200mm disc
Rear brake	Sram Level, 2-piston, Hydraulic Disc Brake, CleanSweep 180mm disc
Tires	Schwalbe SMART-SAM, front 29" x 2.25 / Rear 27.5" x 2.6
Wheels	GMP by Fantic T.Ready
Front hub	Sram 716 RS, 110mm thru-axle
Rear hub	Sram 746 SH, 148mm thru-axle
Handlebar	FSA Logo Ø31.8 L.760mm
Stem	FSA Logo Ø31.8 L.60mm
Seatpost	FSA Logo Ø30.9 L.400mm
Saddle	SelleItalia X-Land Flow