Can-am COMMANDER MAX XT 1000R

HIGHLIGHTS

| PERFORMANCE | Proven Rotax engine Dependable drivetrain Sport segment worthy suspension |
|---------------------------|---|
| WORKABILITY | Rugged taskmaster Work oriented functionality Vehicle protection and rigidity |
| DESIGN & ERGONOMICS | Interior focused on comfort Superior fit and finish Low cost of ownership |
| PLATFORM FEATURES | 120.6 in. (306.3 cm) wheelbase 13 in. (33 cm) of ground clearance 15 in. (38.1 cm) suspension travel 2,000 lb (907.2 kg) towing capacity Dynamic Power Steering (DPS™) Visco-Lokt QE front differential SPORT / ECO™ modes RF D.E.S.S. with Start / Stop button Full roof Premium half doors Mudguards Rear differential with Turf mode |
| SPECIFIC TO XT PACKAGE | 64 in. (162.6 cm) wide with Arched A-arm 28 in. (71.1 cm) XPS Trail King tires 14 in. (35.6 cm) cast-aluminum wheels XT front bumper 4,500 lb (2,041 kg) winch 7.6 in. (19.3 cm) digital display with keypad Can-Am LED signature |



1,930 lb (875.4 kg)

DIMENSIONS / CAPACITIES Estimated Dry Weight *

ENGINE

| Туре | 75 kW (100 hp), Rotax [®] 976 cc, V-twin, liquid cooled |
|----------------------|--|
| Fuel Delivery System | Intelligent Throttle Control (iTC [™]) with Electronic Fuel Injection (EFI) |
| Transmission | Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD with Visco-Lok† QE auto-locking front differential |
| Driving Assistance | Electronic Hill Descent Control SPORT / ECO™ modes |
| Power Steering | Dynamic Power Steering (DPS™) |

ISPENSIONS

| Front Suspension | Arched double A-arm with sway bar / 15 in. (38.1 cm) travel |
|------------------|---|
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Arched TTA with sway bar / 15 in. (38.1 cm) travel |
| Rear Shocks | Twin tube gas charged shocks |
| | |

TIRES / WHEELS

| Front Tires | XPS Trail King 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm) |
|-------------|---|
| Rear Tires | XPS Trail King 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm) |
| Wheels | 14 in. (35.6 cm) cast-aluminum |
| | |

BRAKES

| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
|-------|---|
| Rear | Dual 220 mm disc brakes with hydraulic twin-piston calipers |

| Chassis / Cage | Profiled cage. ROPS approved |
|--|---|
| L×W×H | 160.4 x 64 x 76.2 in (407.3 x 162.6 x 193.5 cm) |
| Wheelbase | 120.6 in. (306.3cm) |
| Ground Clearance | 13 in (33 cm) |
| Cargo Box Dimension | 29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm) |
| Cargo Box Capacity | 600 lb (272.2 kg) |
| Towing Capacity | 2000 lb (907.2 kg) |
| Payload Capacity | 1280 lb (580.6 kg) |
| Storage Capacity | Total: 8.5 gal (32.1 L) Glove Box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and Cup holders: 0.8 gal (3.1 L) Rear console and Cup holders: 1.2 gal (4.5L) Side Cargo Box storage (passenger side): 1.6 gal (5.9 L) Dual-side panel storage: 0.8 gal (3.0 L) |
| Fuel Capacity | 10 gal (38 L) |
| FEATURES | |
| FEATURES Gauge | 7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature |
| | Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine |
| Gauge | Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature |
| Gauge | Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature Lighter type DC outlet in console (10-A) RF Digitally Encoded Security System (D.E.S.S™) |
| Gauge Instrumentation Anti-theft System | Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature Lighter type DC outlet in console (10-A) RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button |
| Gauge Instrumentation Anti-theft System Magneto | Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature Lighter type DC outlet in console (10-A) RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button 650-W Two 55 W reflectors headlights with unique Can-Am LED signature |
| Gauge Instrumentation Anti-theft System Magneto Lighting | Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature Lighter type DC outlet in console (10-A) RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button 650-W Two 55 W reflectors headlights with unique Can-Am LED signature and LED tail lights |
| Gauge Instrumentation Anti-theft System Magneto Lighting Winch | Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT / ECO modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature Lighter type DC outlet in console (10-A) RF Digitally Encoded Security System (D.E.S.S. TM) with Start / Stop button 650-W Two 55 W reflectors headlights with unique Can-Am LED signature and LED tail lights 4,500 lb (2,041 kg) winch with roller fairlead |

WARRANTY & EXTENDED SERVICE

Factory warranty

2-year BRP limited warranty

©2021 Bombardier Recreational Products Inc (BRP). All rights reserved. ^M, * and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. "Base model dry weight shown. 'Visco-Lok is a trademark of GKN Viscodrive GmbH.' All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right, at any time, to discontinue or change specifications, prices, your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs dont mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended that use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

